Smappee Wi-Fi Connect



- Gateway between monitoring system and cloud via Wi-Fi.
- Future-proof thanks to over-the-air updates.
- Cost-effective alternative to the Smappee Genius.
- Ensures secured data storage from components.
- 1-day data storage in case of network outage.

The Wi-Fi Connect is, similar to the Genius, the gateway between the Power Box and the cloud (Smappee or other), ensuring secure data storage from different components. Data is transferred via Wi-Fi. In the event of a network outage, data will be stored for one day. It only transfers data and does not offer smart control or load balancing functionalities. The Wi-Fi Connect is a cost-efficient way to add intelligence to the Smappee Infinity setup.

- **Dimensions:** 55 mm × 55 mm × 26.6 mm $(2.17 \times 2.17 \times 1.05 \text{ inches})$
- Weight: 45 g (1.59 oz)
- Operating temperature: -10 °C to 60 °C (14 °F to 140 °F)
- Storage temperature: -20 °C to 90 °C (-4 °F to 194 °F)
- Relative humidity: 0 % 95 %, non-condensing
- Operating altitude: 0 2,000 m [0 6,562 feet]
- EMC: IEC 61326-1, FCC 47 part 15
- Safety: IEC 60950-1
- Spectrum: EN 300 328 V2.1.1 and EN 300 220

- Product certifications: CE, FCC, RCM
- IP rating (IEC 60529): IP X0
- · Connectivity:
 - Wi-Fi 2.4 GHz
 - RF 433 MHz
 - 2 × Smappee Bus B
- · Accessories included:
 - Wall mounting plate
 - Smappee Bus cable 150 cm (59 inches)

